



**INDOOR  
DISPLAY**

As part of the ultrasonic parking guidance system, IPP-ILD-L72 plays an important role. Unlike video parking guidance, it uses ultrasound to detect the status of parking spaces. IPP-ILD-L72 integrates ultrasonic sensors and LED indicators, and adopts a dual-channel transceiver detection scheme to make the detection results more accurate. It has high stability and low requirements for light efficiency, and can be widely used in hospitals, restaurants, scenic spots, commercial buildings, office buildings and other scenes.

**FEATURES**

- ▶ Wayfinding Parking Signs
- ▶ Easy to Install
- ▶ Easy Understanding
- ▶ Simple and Practical Design
- ▶ Energy Conservation

**TECHNICAL SPECIFICATIONS**

PARAMETER	SPECIFICATIONS		
Product Name	1-Column Display	2-Column Display	3-Column Display
Model Name	IPP-ILD-L72-1	IPP-ILD-L72-2	IPP-ILD-L72-3
Offline Mode	Support parking space counting in case of offline-mode		
Communication Interface	TCP/IP, RS-485		
Display Content	Arrows ("←" "→" "↑" "↓" "↖" "↗") & Numbers (3 Digits, from 0 to 999)		
Font Size	24		
Content Color	Red/Green/Yellow		
Working Temperature	-25°C~65°C		
Power Supply Type	Built-in		
Working Environment	Indoor		
Dimensions (L*W*H)	530mmx287mmx60mm	1017mmx287mmx60mm	1505mmx287mmx60mm

**USA & CANADA**

Tel +1-877-6774040  
info@microlinknet.com  
70 East Sunrise Highway Valley Stream,  
NY 11581, New York

**EUROPE**

Tel +44-20-37695558  
uk@microlinknet.com  
4th Floor, 18 St. Cross Street,  
London, EC1N 8UN

**MIDDLE EAST**

Tel +971 4 556 1557  
mena@microlinknet.com  
Boulevard Plaza Tower One, Level 3,  
Downtown Dubai, United Arab Emirates